

Specification	
Specification Number	80000
Species	Reclaimed Oak
Hardness/Janka	1360
Construction	Engineered
Wear Layer	4mm
Thickness	5/8"
Width	5" (other widths avail)
Lengths	18" to 96" random lengths
Cut	Mixed
Grade	Character - Skip planed
Finish	Natural Oil
Field Applied	No
VOC Compliant	N/A
Certifications available upon request	N/A

**Installation:** On projects inside Texas or Oklahoma please specify as a turnkey (installed) product by Woodwright Hardwood Floor Company to insure correct installation. On projects outside our labor service area, please make note of these important installation guidelines.

- **For Millwork Applications Only!**  
If intended for a wood floor the product will need to be modified.
- Direct glue and blind nail planks to fire rated plywood substrate using polyurethane adhesive such as Bostik BST or equal.
- 5 day acclimation period required prior to installation. It is vital to maintain the HVAC Envelope to a +/- 5% Relative Humidity within the NWFA recommended range. Failure to follow these guidelines could void warranty.

**Specie:** Reclaimed Oak is an open grain reclaimed wood with high color and texture variation. The skip plan texture is an approx. 50/50 mix of saw mark texture and surfaced.

Small splits, checks, open knots, worm holes and nails holes that could expose the core are all acceptable characteristics.

**Cut:** Mixed

**Grade:** Character – Skip Planed texture

**Warranty:** This product is intended for millwork applications only. It carries a lifetime structural warranty and one year finish warranty.

**Images:** For additional images, please contact us at [sales@woodwright.net](mailto:sales@woodwright.net).

