

Specification	
Specification Number	82000
Species	Reclaimed Mushroom Wood – Sculpted face
Hardness/Janka	1360
Construction	Solid
Wear Layer	N/A
Thickness	1" Nominal
Width	5" Nominal
Lengths	2' to 12'
Cut	Flat sawn
Grade	Character
Finish	Unfinished
Field Applied	No
VOC Compliant	N/A
Certifications Available	Available as FSC Recycled

**Installation:** On projects inside Texas or Oklahoma please specify as a turnkey (installed) product by Woodwright Hardwood Floor Company to insure correct installation. On projects outside our labor service area, please make note of these important installation guidelines.

- **For Millwork Applications Only!**  
If intended for a wood floor the product will need to be modified.
- Direct glue and blind nail planks to fire rated plywood substrate using polyurethane adhesive such as Bostik BST or equal.
- 5 day acclimation period required prior to installation. It is vital to maintain the HVAC Envelope to a +/- 5% Relative Humidity within the NWFA recommended range. Failure to follow these guidelines could void warranty.

**Specie:** Reclaimed Mushroom Wood is salvaged from disassembled Mushroom Beds. It has a unique sculpted face texture created by enzymes eating away at the wood surface prior to power washing. Expect lots of natural characteristic marks such as knots and small cracks.

**Cut:** Flat Sawn

**Grade:** Character

**Warranty:** This product is intended for millwork applications only and is sold unfinished.

**Images:** For additional images, please contact us at [sales@woodwright.net](mailto:sales@woodwright.net).

